

THE SUNN® 412 LOUDSPEAKER ENCLOSURE

Your new Sunn 412 Loudspeaker Enclosure is constructed from 5/8" (1.6 cm) 11-ply Birch Plywood and is capable of handling up to 300 Watts of powerful clean sound. The Sunn 412 features four 12" (30.5cm) speakers with 54 oz (1.53 kg) magnets and is designed for use with the Sunn Model T or any other professional quality instrument amplifier. In order to more fully understand the operational characteristics of your Sunn 412 loudspeaker enclosure, please read through all instructions and heed all caution and safety warnings on both your amplifier and Sunn 412 loudspeaker enclosure.

CONNECTING MULTIPLE 412 LOUDSPEAKER ENCLOSURES

Because the Sunn 412 Loudspeaker Enclosure's jacks are wired in parallel, multiple 412 cabinets can be "daisy chained" together providing additional output for larger venues. To do so, simply connect them by inserting a speaker cable (16 gauge or larger) with a 1/4" plug into the input jacks on the rear panel of each cabinet. *Note: If using a tube amplifier, your tube amp could fall into protect mode or even be damaged by using an improper impedance load. Therefore, it is important to heed all caution and safety warnings on both your amplifier and Sunn 412 loudspeaker enclosure.*

From
AMP



SPECIFICATIONS

PART NUMBER	021-1675-000
DRIVERS	Four 12 " (30.5 cm) Steel Frame Drivers 1 3/4" (4.5 cm) voice coils 54 ounce (1.53 kg) magnets
CABINET	5/8 " (1.6 cm) 11-ply Birch Plywood
SENSITIVITY	96 dB, 1 Watt - 1 Meter
POWER HANDLING	300 Watts
IMPEDANCE	16Ω
CONNECTIONS	Dual, Parallel Wired, 1/4" High Current Input Jacks
ENCLOSURE VOLUME	V _B = 5.2 ft ³ (147 l)
DIMENSIONS	Height: 30 in. (76.2 cm) Width: 30 in. (76.2 cm) Depth: 15 in. (38.1 cm)
WEIGHT	99 lbs. (45.0 kg)

A PRODUCT OF:
FENDER MUSICAL INSTRUMENTS CORP.
CORONA, CA 91720 USA