

SOUND REINFORCEMENT PRODUCTS PROFESSIONAL STAGE LIGHTING

Effective September 16, 1991

Suggested Retail PRICE LIST

SUNN SOUND REINFORCEMENT

PORTABLE POWERED MIXERS

The SR Powered mixers represent a remarkable value in professional features and performance. Ideal for sound reinforcement, keyboard and other amplification at affordable prices.

71-4150-000

SR 4150 -----

\$ 499.99

150 watts RMS into 4 ohms, 4 channels each with high and low impedance inputs, high and low EQ, Eff/Reverb and Monitor send and channel gain.

The Master section features 5-band Graphic EQ, Main, Monitor and Reverb gain controls and a versatile patch panel that includes Tape. EQ, and Aux in and out jacks.

071-6521-000

SR 6520P-----

829.99

520 watts RMS into 2 ohms, 350 watts RMS into 4 ohms, 6 channels each with high and balanced low impedance inputs, Eff/Reverb and Monitor sends and channel gain, 3-band EQ per input channel

The Master section features 9-band Graphic EQ, Reverb, Compressor, Main, Monitor and Reverb gain controls and a versatile patch panel that includes Tape, EQ and Aux In and Out jacks, Fan Cooling, Reverb to Monitors, Phantom Power (switchable), "Deltacomp" power amp compression.

071-8521-000

SR 8520P -----

899.99

520 watts RMS into 2 ohms, 350 watts RMS into 4 ohms, 8 channels each with high and balanced low impedance inputs, Eff/Reverb and Monitor sends and channel gain, 3-band EQ per input channel.

The Master section features 9-band Graphic EQ, Reverb, Compressor. Main, Monitor and Reverb gain controls and a versatile patch panel that includes Tape, EQ and Aux In and Out jacks, Fan Cooling, Reverb to Monitors, Phantom Power (switchable), "Deltacomp" power amp compression.

MIXING CONSOLES

POWERED MIXING CONSOLES

The Sunn PX Series features the latest advances in technology and versatility and includes all of your requirements built into one compact package. High quality, reliable products designed for applications where an all-in-one mixer/amplifier is needed.

071-2108-000 PX 2108 -----

----- 1649.99

250 watts per channel into 4 ohms, 8 channels each with high and balanced low impedance inputs, trim control, 3 separate sends (Eff/Reverb, Monitor and Aux) with internal jumper for Pre/Post assignment, 3-band EQ, pan and channel fader, fan cooling.

The Master section features dual 10-band Graphic EQ, Phantom power, 2 switchable LED bar graphs, Reverb, switchable compression, 4 precision master faders (program L/R, Main and Monitor). Additional features include channel in and out patch points, direct in jacks and extensive back panel patching capabilities.

		071-2112-000	PX 2112	1899.99
			250 watts per channel into 4 ohms, 12 channels each with high and balanced low impedance inputs, trim control, 3 separate sends (Eff/Reverb, Monitor and Aux) with internal jumper for Pre/Post	
			assignment, 3-band EQ, pan and channel fader, fan cooling.	
			The Master section features dual 10-band Graphic EQ, Phantom power, 2 switchable LED bar graphs, Reverb, switchable compression, 4 precision master faders (program L/R, Main and Monitor).	
			Additional features include channel in and out patch points, direct in jacks and extensive back panel patching capabilities.	
	inc e	071-2116-000	PX 2116	2199.99
in the	8.JF	Carrison Telepo	250 watts per channel into 4 ohms, 16 channels each with high and balanced low impedance inputs, trim control, 3 separate sends (Eff/Reverb, Monitor and Aux) with internal jumper for Pre/Post assignment, 3-band EQ, pan and channel fader, fan cooling.	
			The Master section features dual 10-band Graphic EQ, Phantom power, 2 switchable LED bar graphs, Reverb, switchable compression, 4 precision master faders (program L/R, Main and Monitor).	
			Additional features include channel in and out patch points, direct in jacks and extensive back panel patching capabilities.	
living Co	neoloe			
	MX Ser	ies offers unpara	alled price/performance features and is ideal for portable sound reinforcenes or theatres. Sunn power amplifiers, equalizers, electronic crossovers	
The Sunn I	MX Ser stalled s	ies offers unpara systems in church	alled price/performance features and is ideal for portable sound reinforcenes or theatres. Sunn power amplifiers, equalizers, electronic crossovers to complete your system requirements.	
he Sunn lent or ins	MX Ser stalled s	ies offers unpara systems in church	nes or theatres. Sunn power amplifiers, equalizers, electronic crossovers it to complete your system requirements.	419.9
The Sunn I	MX Ser stalled s	ies offers unpara systems in church ems are designed	nes or theatres. Sunn power amplifiers, equalizers, electronic crossovers it to complete your system requirements.	419.9
he Sunn lent or ins	MX Ser stalled s	ies offers unpara systems in church ems are designed	nes or theatres. Sunn power amplifiers, equalizers, electronic crossovers to complete your system requirements. PSM-8 Personal Stereo Mixer, includes 8 input channels, each with Trim,	419.9
The Sunn I	MX Ser stalled s	ies offers unpara systems in church ems are designed	PSM-8	
The Sunn I	MX Ser stalled s	ies offers unpara systems in church ems are designed 071-0108-000	PSM-8	419.99 899.9
The Sunn I	MX Ser stalled s	ies offers unpara systems in church ems are designed 071-0108-000	PSM-8	899.9
The Sunn I	MX Ser stalled s	ies offers unpara systems in church ems are designed 071-0108-000	PSM-8	899.9
The Sunn I	MX Ser stalled s	ies offers unpara systems in church ems are designed 071-0108-000	PSM-8	

071-4208-000	MX 4208	1249.99
071-4200-000	8 channels each with high and balanced low impedance inputs, trim control, 3-band EQ, 3 send busses (Eff/Reverb, Monitor and Aux) with internal jumper for Pre/Post assignment, Pan, individual cue buss, and precision channel fader.	1249.99
	The Master section features Phantom power, Reverb, 2 switchable LED bar graphs, 4 master faders (program L/R, Main, Monitor), complete compliment of return controls, and Cue with headphone jack and level control.	
	Additional features include individual channel in and out patch points, direct in jacks and extensive back panel patching capabilities.	44
071-4212-000	MX 4212	1499.99
lepevibnik et "mili skle	12 channels each with high and balanced low impedance inputs, trim control, 3-band EQ, 3 send busses (Eff/Reverb, Monitor and Aux) with internal jumper for Pre/Post assignment, Pan, individual cue buss, and precision channel fader.	e MASTIN Post Brack Inchargen
	The Master section features Phantom power, Reverb, 2 switchable LED bar graphs, 4 master faders (program L/R, Main, Monitor), complete compliment of return controls, and Cue with headphone jack and level control.	
	Additional features include individual channel in and out patch points, direct in jacks and extensive back panel patching capabilities.	
071-4216-000	MX 4216	1799.99
nacutari Legul a temple -	16 channels each with high and balanced low impedance inputs, trim control, 3-band EQ, 3 send busses (Eff/Reverb, Monitor and Aux) with internal jumper for Pre/Post assignment, Pan, individual cue buss, and precision channel fader.	1700.00
The state of the s	The Master section features Phantom power, Reverb, 2 switchable LED bar graphs, 4 master faders (program L/R, Main, Monitor), complete compliment of return controls, and Cue with headphone jack and level control.	
	Additional features include individual channel in and out patch points, direct in jacks and extensive back panel patching capabilities.	
SIGNAL PROCESSING		
Sunn signal processing products are professional control for your system Equalizers	e designed with the latest advances in technology to provide reliable, equalization requirements.	
071-3200-000	SP 3200	429.99
	30 band equalizer on ISO frequency centers, with switchable 6/12dB cut or boost, variable high pass filter, bypass switch, +24dBV output, level control, balanced 1/4" and XLR connectors.	
071-3215-000	SP 3215	429.99
071-3213-000	Dual 15 band, 2/3rd-octave EQ, with switchable 6/12dB cut or boost, variable high pass filter, bypass switch, +24dBV output, level control, balanced 1/4" and XLR connectors	429.39
071-3202-000	SP 3202	- 600 00
071-3202-000	Dual 30 band equalizeron ISO frequency centers, with switchable 6/12dB cut or boost, variable high pass filter, bypass switch, +24dBV output, level control, balanced 1/4" and XLR connectors.	633.33

POWER AMPLIFIERS

Sunn SPL series power amplifiers provide one of the finest power/performance priced products available. Designed for the touring professional and for installed systems the SPL power amplifiers offer unsurpassed reliablility at very affordable prices.

Tonasinty o	at very aπordable prices.	and the second control of the second	
	071-7250-000	SPL 7250	779.99
	071-7450-000	SPL 7450	929.99
SPEAKER	SYSTEMS	450 watts per channel into 4 ohms at 0.03% THD, 20Hz to 20kHz, 900 watts into 8 ohms in bridged mode, forced air cooling, 1/4" balanced RTS phone jacks and balanced XLR connectors, turn on/off delay, 2-speed fan cooling.	anima.
Sunn spea	ker systems provide full on with reliability and pow	dynamic range for today's electronic musical world. Music and vocal er handling performance you can count on.	
2 way oys	071-1110-000	1110 10" bass speaker with dual piezo drivers and 2 section horn,16 ohm impedance, 94dB sensitivity at 1 meter watt, 100 watts power	199.99
		handling, 60Hz to 20kHz frequency response, stand adapter included	
	071-1201-000	1201	269.99
	071-1205-000	1205	299.99
k	071-1211-000	1211	449.99
		15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, carpet covering. Stand adapter included.	
+	071-1225-000	SPL 1225	599.99
		cast frame 15" bass speaker with 3" voice coil, compression driver with constant directivity horn, 8 ohm impedance, 100dB sensitivity at 1 meter watt, 200 watts power handling, 50Hz to 20kHz frequency response, Birch plywood cabinet in trapezoid configuration, biampready third order Butterworth crossover.	
*	071-1226-000	SPL 1226	799.99
*	071-1228-000	1228	599.99

	071-1272-000	1272	269.
	'	12" bass speaker with dual piezo drivers and two section horn,	
		16 ohm impedance, 95dB sensitivity at 1 meter watt, 100 watts	
		power handling, 60Hz to 20kHz frequency response, level control,	
		30 or 60 degree tilt angles.	
	074 4077 000	n retenues the tenues by enough and	19 7
	071-1275-000	15" been appared with dual pions drivers and two section been	299.
		15" bass speaker with dual piezo drivers and two section horn, 16 ohm impedance, 95dB sensitivity at 1 meter watt, 100 watts	
		power handling, 60Hz to 20kHz frequency response, level control,	
		30 or 60 degree tilt angles.	
	EN CHILDREN	s or in the second seco	
	071-1282-000	SPL 1282	529.
		12" cast frame bass speaker with 3" voice coil, compression driver	
		with constant directivity horn, 8 ohm impedance, 100dB sensitivity	
		at 1 meter watt, 150 watts power handling, 60Hz to 20kHz frequency	
		response, Biamp-ready third order Butterworth crossover, Birch plywood cabinet with 30 or 60 degree tilt angle	
		Birch plywood cabinet with 30 or 60 degree tilt angle	
	071-1285-000	SPL 1285	579.
		15" cast frame bass speaker with 3" voice coil, compression driver	
		with constant directivity horn, 8 ohm impedance, 100 dB sensitivity	
		at 1 meter watt, 200 watts power handling, 50Hz to 20kHz frequency	
		response, Biamp-ready third order Butterworth crossover,	
		Birch plywood cabinet with 30 or 60 degree tilt angles	
CL SERIES (C	ontractor/Installer)		
O.I. OLITICS (O	071-1295-000	1295 C.I	399.
	0	15" bass speaker with dual piezo drivers and two section horn, 8 ohm	000.
		impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling,	
Z Carrier		60Hz to 20kHz ±6dB frequency response, wood veneer finish,	
		brown grill cloth.	
	074 4004 000	14004 0 1 100 100 100 100 100 100 100 10	
	071-1291-000	1291 C.I	499.
	071-1291-000	15" bass speaker, compression driver with constant directivity horn,	499
10.483	071-1291-000	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power	499
10: 881	071-1291-000	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish,	499
n(+ 28)	071-1291-000	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power	499.
10 481	071-1291-000	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish, brown grill cloth. 1292M C.I	
	and and the second	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish, brown grill cloth. 1292M C.I	
	and and the second	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish, brown grill cloth. 1292M C.I	
ACCESSORIES	071-1292-000	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish, brown grill cloth. 1292M C.I	
ACCESSORIES Rack Cabinets	071-1292-000	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish, brown grill cloth. 1292M C.I	
ACCESSORIES Rack Cabinets	071-1292-000	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish, brown grill cloth. 1292M C.I. ——————————————————————————————————	349.
	071-1292-000	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish, brown grill cloth. 1292M C.I	349. 149.
	071-1292-000 071-1904-000	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish, brown grill cloth. 1292M C.I. ——————————————————————————————————	349. 149. 189.
Rack Cabinets	071-1292-000 071-1904-000 071-1908-000	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish, brown grill cloth. 1292M C.I	349 149 189 229
	071-1292-000 071-1904-000 071-1908-000 071-1912-000 071-1916-000	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish, brown grill cloth. 1292M C.I	149. 189. 229. 269.
Rack Cabinets	071-1292-000 071-1904-000 071-1908-000 071-1912-000	15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish, brown grill cloth. 1292M C.I	149. 149. 189. 229. 269.

Special Note: Products indicated with (*) exceed the maximum UPS requirements for size and/or weight and must be shipped via common carrier

PROFESSIONAL STAGE LIGHTING

	990-9900-330	SC24-F	239.9
	330-3300-000	Two scene, 4 channel with Sunnplex mic cable connect system,	
		variable brightness and fade rates, all flash button, audio sync,	
		remote or footswitch operation.	
	990-9900-390	SC28-F	329.9
797	Thurst transcent and a second	Two scene, 8 channel with Sunnplex mic cable connect system,	
		crossfade, flash buttons, master level, audio sync.	
	990-9900-350	SC216,	449.
NAT .		Two scene, 16 channel with Sunnplex mic cable connect system,	
		crossfade, flash buttons, master level, audio sync.	
		NOOLEO TERRETERIA DE LA	
OGRAMMABLE	CONTROL COI	PLC 816e	679.
	990-9900-420	Programmable Lighting Controller with 101 user-programmable	0,0.
		scenes, song mode, controls up to 16 independent channels,	
		MIDI in/out/thru ports, programmable audio sync and chase,	
		Cuppelov interface	
	990-9900-320		1799.
10019	230 0000 020	Programmable Lighting Controller with 101 user programmable	
		scenes, 10 key pad for data entry, 32 channels, 4 channels for	
		special effects, MIDI in/out/thru ports, U.S.I.T.T. interface protocol	
		AMX 192 and DMX 512, audio sync, programmable chase, Sunnplex	
		interface, up to 36 programmable sub masters.	
		Accuse the Colonia with the application of the Colonia Colonia Colonia Colonia Colonia Colonia Colonia Colonia	
MMER PACKS	(Truss or Tree N	Mount) PS310	349
	080-0310-000	Four channel (32 jumper select programmable channels), 300 watts	343
		per channel, with Sunnplex mic cable connect system.	
	080-0610-000	PS610	399
	080-0810-000	Four channel (32 jumper select programmable channels), 600 watts	
		per channel, with Sunnplex mic cable connect system.	
	990-9900-340	PS1200	489
(41)	000 0000 0 10	Four channel (32 jumper select programmable channels), 1200 watts	
		per channel, with Sunnplex mic cable connect system.	
		Same the substitution of the section of the section of	
MMER PACKS		Same specifications as 1972 his collection	400
	080-0640-000	PSR 640	499
	000 1000 000	Four channels, 600 watts per channel, Sunnplex interface, 1 rack space.	999
	080-1208-000	PSK 1208	223
		Fight channels 1900 watte per channel dual 190 volt or 990 volt	
		Eight channels, 1200 watts per channel, dual 120 volt or 220 volt	
		terminal block, Sunnplex and 0-10 volt control interface, 3 rack spaces,	
. At	080 0600 000	terminal block, Sunnplex and 0-10 volt control interface, 3 rack spaces, fan cooled.	529.9
	080-0600-000	terminal block, Sunnplex and 0-10 volt control interface, 3 rack spaces, fan cooled. PRO RACK ND 600	529.9
	080-0600-000	terminal block, Sunnplex and 0-10 volt control interface, 3 rack spaces, fan cooled. PRO RACK ND 600	
		terminal block, Sunnplex and 0-10 volt control interface, 3 rack spaces, fan cooled. PRO RACK ND 600	
	080-0600-000	terminal block, Sunnplex and 0-10 volt control interface, 3 rack spaces, fan cooled. PRO RACK ND 600	
		terminal block, Sunnplex and 0-10 volt control interface, 3 rack spaces, fan cooled. PRO RACK ND 600	
		terminal block, Sunnplex and 0-10 volt control interface, 3 rack spaces, fan cooled. PRO RACK ND 600	1399.9
	080-0812-000	terminal block, Sunnplex and 0-10 volt control interface, 3 rack spaces, fan cooled. PRO RACK ND 600	1399.9
		terminal block, Sunnplex and 0-10 volt control interface, 3 rack spaces, fan cooled. PRO RACK ND 600	

LIGHT GROUPS	
990-9900-	260 LG-4 399.99
	Four PAR 38 light fixtures, four 150 watt bulbs, gel frames, assorted colored gels and truss bar with stand adaptor.
ACCESSORIES	
990-9900-	
	Tripod stand constructed of anodized aluminum alloy tubing, 100 lb. capacity.
990-9900-	
	Four foot cross bar, drilled for fixture mounting, anodized aluminum alloy tubing.
990-9900-	
	Lighting fixture includes gel frame, six foot cord.
990-9900-	
990-9900-	Lighting fixture includes gel frame, six foot cord. 640 PAR 64
990-9900-	Lighting fixture includes gel frame, six foot cord.
990-9900-	
	One each of four assorted colors.
990-9900-	
	One each of 20" x 24" gels of four assorted colors.
990-9900-	
	Rack mountable (one rack space). Translates Sunnplex
	Multiplexing System to 16 discrete channels of 0 to 10 volts.
1.41400	Allows Sunn controller to talk to other brand dimmers.
LAMPS 990-9900-	180 150, 150 Watt Par 38 12.99
990-9900-	
990-9900-	
990-9900-	
990-9900-	
990-9900-	



SOUND REINFORCEMENT PRODUCTS PROFESSIONAL STAGE LIGHTING

Effective September 16, 1991

Suggested Retail PRICE LIST