

Contents

SUNN SOUND REINFORCEMENT

Portable Powered Mixers 1 Mixing Consoles 2, 3, 4, 5, 6 Signal Processing 6 Power Amplifiers 6, 7 Speaker Systems 7, 8, 9 Accessories 9 **PROFESSIONAL STAGE LIGHTING** Manual Control Consoles 10 Programmable Control Consoles 10 Dimmer Packs 10, 11 Light Groups 11 Accessories 11 Lamps 12



The Sound Choice for over 25 years, providing quality products to the music industry.

Sunn Sound Reinforcement

PORTABLE POWERED MIXERS

The SR Powered mixers represent a remarkable value in professional features and performance. Ideal for sound reinforcement, keyboard and other amplification at affordable prices.

071-4150-000	SR 4150, 150 watts RMS into 459.99 4 ohms, 4 channels each with high and low impedance inputs, high and low EQ, Eff/Reverb and Monitor send and channel gain.
	The Master section features 5-band Graphic EQ, Main, Monitor and Reverb gain controls and a versatile patch panel that includes Tape, EQ, and Aux in and out jacks.
071-6520-000	SR 6520, 520 watts RMS into 769.99 2 ohms, 350 watts RMS into 4 ohms, 6 channels each with high and balanced low impedance inputs, high and low EQ, Eff/Reverb and Monitor sends and channel gain.
	The Master section features 9-band Graphic EQ, Reverb, Compressor, Main, Monitor and Reverb gain controls and a versatile patch panel that includes Tape, EQ and Aux In and Out jacks, fan cooling, Reverb to Monitors
071-8520-000	SR 8520, 520 watts RMS into 869.99 2 ohms, 350 watts RMS into 4 ohms, 8 channels each with high and balanced low impedance inputs, high and low EQ, Eff/Reverb and Monitor sends and channel gain.
2	The Master section features 9-band Graphic EQ, Reverb, Compressor, Main, Monitor and Reverb gain controls and a versatile patch panel that includes Tape, EQ and Aux In and Out jacks, fan cooling, Reverb to Monitors.

Prices and specifications subject to change without notice

MIXING CONSOLES

Powered Mixing Consoles

The Sunn PX Series features the latest advances in technology and versatility and includes all of your requirements built into one compact package. High quality, reliable products designed for applications where an all-in-one mixer/amplifier is needed.

071-2108-000

PX 2108, 250 watts per channel 1649.99 into 4 ohms, 8 channels each with high and balanced low impedance inputs, trim control, 3 separate sends (Eff/Reverb, Monitor and Aux) with internal jumper for Pre/ Post assignment, 3-band EQ, pan and channel fader, fan cooling.

The Master section features dual 10-band Graphic EQ, Phantom power, 2 switchable LED bar graphs, Reverb, switchable compression, 4 precision master faders (Program L/R, Main and Monitor).

Additional features include channel in and out patch points, direct in jacks and extensive back panel patching capabilities.

071-2112-000

PX 2112, 250 watts per channel **1849.99** into 4 ohms, 12 channels each with high and **balanced** low impedance inputs, trim control, 3 separate sends (Eff/Reverb, Monitor and Aux) with internal jumper for Pre/ Post assignment, 3-band EQ, pan and channel fader, fan cooling.

The Master section features dual 10-band Graphic EQ, Phantom power, 2 switchable LED bar graphs, Reverb, switchable compression, 4 precision master faders (Program L/R, Main and Monitor).

Additional features include channel in and out patch points, direct in jacks and extensive back panel patching capabilities. 071-2116-000

PX 2116, 250 watts per channel 2149.99 into 4 ohms, 16 channels each with high and balanced low impedance inputs, trim control, 3 separate sends (Eff/Reverb, Monitor and Aux) with internal jumper for Pre/Post assignment, 3-band EQ, pan and channel fader, fan cooling.

The Master section features dual 10-band Graphic EQ, Phantom power, 2 switchable LED bar graphs, Reverb, switchable compression, 4 precision master faders (Program L/R, Main and Monitor).

Additional features include channel in and out patch points, direct in jacks and extensive back panel patching capabilities.

Mixing Consoles

The Sunn MX Series offers unparalled price/performance features and is ideal for portable sound reinforcement or installed systems in churches or theatres. Sunn power amplifiers, equalizers, electronic crossovers and speaker systems are designed to complete your system requirements.

071-0108-000	PSM-8 , Personal Stereo Mixer, 419.99 includes 8 input channels, each with Trim, Effects Send, Bass and Treble controls, and Pan control.
	Master section includes Master faders, Aux and Effects Returns, and Headphone output.
071-4110-000	RMX 4110, Rack Mount Mixer, 10 input channels, stereo and summed mono outputs (balanced & unbalanced outputs). Monitor, Effects and Aux (3 busses total), 3 stereo return lines, 3-band EQ, trim control, 6 rack spaces, three 12 segment LED output displays
071-4108-000	MX 4108, 8 channels each with 829.99 high and balanced low impedance inputs, 3-band EQ, trim control, Monitor and Eff/Reverb sends, pan and channel fader.

2

	The Master section includes Phantom power, Reverb, 2 V.U. meters (switchable L/R Main/Mon), 4 master faders, headphone jack with level control. Additional features include channel patch, Monitor and Effects direct in, Effects send and return to Main/	071-4208-000	MX 4208, 8 channels each with 1249.99 high and balanced low impedance inputs, trim control, 3-band EQ, 3 send busses (Eff/Reverb, Monitor and Aux) with internal jumper for Pre/Post assignment, Pan, individual cue buss, and precision channel fader.
)71-4112-000	Mon, program L/R or Main only. MX 4112, 12 channels each with 1039.99 high and balanced low impedance inputs, 3-band EQ, trim control, Monitor and Eff/Reverb sends, pan and channel fader.	•	The Master section features Phantom power, Reverb, 2 switchable LED bar graphs, 4 master faders (Program L/R, Main, Monitor), complete compliment of return controls, and Cue with headphone jack and level control.
	The Master section includes Phantom power, Reverb, 2 V.U. meters (switchable L/R Main/Mon), 4 master faders, headphone jack with level control.		Additional features include individual channel in and out patch points, direct in jacks and extensive back panel patching capabilities.
071-4116-000	Additional features include channel patch, Monitor and Effects direct in, Effects send and return to Main/ Mon, program L/R or Main only. MX 4116 , 16 channels each with 1249.99 high and balanced low impedance	071-4212-000	MX 4212, 12 channels each with 1449.99 high and balanced low impedance inputs, trim control, 3-band EQ, 3 send busses (Eff/Reverb, Monitor and Aux) with internal jumper for Pre/Post assignment, Pan, individual cue buss, and precision channel fader.
	inputs, 3-band EQ, trim control, Monitor and Eff/Reverb sends, pan and channel fader. The Master section includes Phantom power, Reverb, 2 V.U. meters (switchable L/R Main/Mon), 4 master faders, headphone jack with level control.		The Master section features Phantom power, Reverb, 2 switchable LED bar graphs, 4 master faders (Program L/R, Main, Monitor), complete compliment of return controls, and Cue with headphone jack and level control.
	Additional features include channel patch, Monitor and Effects direct in, Effects send and return to Main/ Mon, program L/R or Main only.		Additional features include individual channel in and out patch points, direct in jacks and extensive back panel patching capabilities.
		071-4216-000	MX 4216, 16 channels each with 1749.99 high and balanced low impedance inputs, trim control, 3-band EQ, 3 send busses (Eff/Reverb, Monitor and Aux) with internal jumper for Pre/Post assignment, Pan, individual cue buss, and precision channel fader.

The Master section features Phantom power, Reverb, 2 switchable LED bar graphs, 4 master faders (Program L/R, Main, Monitor), complete compliment of return controls, and Cue with headphone jack and level control.

Additional features include individual channel in and out patch points, direct in jacks and extensive back panel patching capabilities.

SIGNAL PROCESSING

Sunn signal processing products are designed with the latest advances in technology to provide reliable, professional control for your system equalization and crossover requirements.

Equalizers

071-3200-000	SP 3200, 30 band equalizer on 399.99 ISO frequency centers, with switchable 6/12dB cut or boost, variable high pass filter, bypass switch, +24dBV output, level control, balanced 1/4" and XLR connectors.		071
071-3215-000	SP 3215, Dual 15 band, two 399.99 thirds octave EQ, with switchable 6/12dB cut or boost, variable high pass filter, bypass switch, +24dBV output, level control, balanced 1/4" and XLR connectors		071
071-3202-000	SP 3202, Dual 30 band equalizer 649.99 on ISO frequency centers, with switchable 6/12dB cut or boost, variable high pass filter, bypass switch, +24dBV output, level control, balanced 1/4" and XLR connectors.		
		:	* 071
POWER AMPLIFIE Sunn SPL series po	ERS wer amplifiers provide one of the finest power/	Ŋ	
professional and fo	I products available. Designed for the touring r installed systems the SPL power amplifiers reliablility at very affordable prices.	9	

071-7250-000	SPL 7250, 250 watts per	749.99
	channel into 4 ohms at 0.03 THD,	
	20Hz to 20kHz, 440 watts into 8	
	ohms in bridged mode, 1/4"	
	balanced RTS phone jacks and	
	balanced XLR connectors, turn on/	
	off delay, switchable compressor,	
·····································	2-speed fan cooling.	

071-7350-000

SPL 7350, 375 watts per 899.99 channel into 4 ohms at 0.03 THD, 20Hz to 20kHz, 750 watts into 8 ohms in bridged mode, forced air cooling, 1/4" balanced RTS phone jacks and balanced XLR connectors, turn on/off delay, 2-speed fan cooling. U.L. listed.

SPEAKER SYSTEMS

Sunn speaker systems provide full dynamic range for today's electronic musical world. Music and vocal reproduction with reliability and power handling performance you can count on.

	2-way Systems		
	071-1201-000	1201, 12" bass speaker with dual piezo drivers and two section horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 100 watts power handling, 60Hz to 20kHz frequency response. Stand adapter included.	249.99
	071-1205-000	1205, 15" bass speaker with dual piezo drivers and two section horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 60Hz to 20kHz \pm 6dB frequency response. Stand adapter included.	289.99
	071-1295-000	1295 Cl, 15" bass speaker with dual piezo drivers and two section horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 60Hz to 20kHz \pm 6dB frequency response, wood veneer finish, brown grill cloth. Stand adapter included.	399.99
3	*071-1211-000	1211, 15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, carpet covering. Stand adapter included.	399.99
	* 071-1291-000	1291 Cl , 15" bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95dB sensitivity at 1 meter watt, 150 watts power handling, 50Hz to 20kHz frequency response, wood veneer finish, brown grill cloth.	499.99

7

*071-1225-000	SPL 1225, cast frame 15" bass speaker with 3" voice coil, compression driver with constant directivity horn, 8 ohm impedance, 100dB sensitivity at 1 meter watt, 200 watts power handling, 50Hz to 20kHz frequency response, Birch plywood cabinet in trapezoid configuration, biamp-ready third order Butterworth crossover.		071-1282-000	SPL 1282, 12" cast frame bass speaker with 3" voice coil, compress sion driver with constant directivity horn, 8 ohm impedance, 100dB sensitivity at 1 meter watt, 150 watts power handling, 60Hz to 20kHz frequency response, Biamp-ready third order Butterworth crossover, plywood cabinet with 30 or 60 degree tilt angle	
* 071-1226-000	SPL 1226, 2 cast frame 15" bass speakers with 3" voice coils, compression drivers with constant directivity horns, 8 ohm impedance, 100dB sensitivity at 1 meter watt, 400 watts power handling, 38Hz to 20kHz frequency response, Birch plywood cabinet in trapezoid configuration, biamp-ready third order Butterworth crossover.		* 071-1285-000	SPL 1285, 15" cast frame bass speaker with 3" voice coil, compress sion driver with constant directivity horn, 8 ohm impedance, 100 dB sensitivity at 1 meter watt, 200 watts power handling, 50Hz to 20kHz frequency response, Biamp-ready third order Butterworth crossover, plywood cabinet with 30 or 60 degree tilt angles.	
* 071-1228-000	1228 , 18" cast frame bass speaker, compression driver with constant directivity horn, 8 ohm impedance, 95db sensitivity at 1 meter watt, 150 watts power handlling, 45Hz to 20kHz fre- quency response.	599.99	ACCESSORIES Rack Cabinets 071-1904-000 071-1908-000 * 071-1912-000 * 071-1916-000	RX 1904 , 4-space rack RX 1908 , 8-space rack RX 1912 , 12-space rack RX 1916 , 16-space rack	129.99 149.99 189.99 219.99
Monitor Systems 071-1272-000	1272 , 12" bass speaker with dual piezo drivers and two section horn, 16 ohm impedance, 95dB sensitivity at 1 meter watt, 100 watts power handling, 60Hz to 20kHz frequency response, level control, 30 or 60 degree tilt angles.	у	Speaker Stand 071-0270-000	ST-75 , Tripod stand constructed of anodized aluminum alloy tubing, 75 lb. capacity.	159.99
071-1275-000	1275 , 15" bass speaker with dual piezo drivers and two section horn, 16 ohm impedance, 95dB sensitivity at 1 meter watt, 100 watts power handling, 60Hz to 20kHz frequency response, level control, 30 or 60 degree tilt angles.	y ,			
	roducts indicated with (*) exceed the r rements for size and/or weight and mu amon carrier.				
	8			9	

Professional Stage Lighting

080-1208

PSR 1208, Eight channels,

1200 watts per channel, dual 120 volt

999.99

529.99B

1349.99B

1849.99B

399.99

\$169.99

69.99

67.99

71.99

76.99 17.99

49.99

279.99

	fortal otago Light	.9		or 220 volt terminal block, Sunnplex	
MANUAL CON	TROL CONSOLES			and 0-10 volt control interface, 3 rac	
990-9900-330		209.99		spaces, fan cooled.	
1.1.1. Sacres	with Sunnplex mic cable connect syste	em,	080-0600	PRO RACK ND 600, 4 channel	529.9
	variable brightness and fade rates, all			non-dim power pack, 600 watts per	
	flash button, audio sync, remote or			channel, Sunnplex and 0-10 volt	
	footswitch operation.			interface, 2 rack spaces.	
000 0000 200		299.99	080-0812		349.9
990-9900-390			000 0012	1200 watts per channel, SCR circuit	
	with Sunnplex mic cable connect syste			Sunnplex, DMX 512 and 0-10 volt	**
	crossfade, flash buttons, master level,			control interfaces, Toroidal filters,	
	audio sync.	000 00		magnetic circuit breakers, 3 rack	
990-9900-350		399.99			
	with Sunnplex mic cable connect syste		000 0004	spaces, fan cooled.	
	crossfade, flash buttons, master level,		080-0824		849.9
	audio sync.			2400 watts per channel, SCR circuit	1,
				Sunnplex, DMX 512 and 0-10 volt	
PROGRAMMAI	BLE CONTROL CONSOLES			control interfaces, Toroidal filters,	
990-9900-420	PLC 816e, Programmable Lighting	629.99		magnetic circuit breakers, 3 rack	
	Controller with 101 user-programmable			spaces, fan cooled.	
	scenes, song mode, controls up to 16				
	independent channels, MIDI in/out/thru	1	LIGHT GROUPS	5	
	ports, programmable audio sync and		990-9900-260	LG-4, Four PAR 38 light fixtures,	399
	chase, Sunnplex interface.			four 150 watt bulbs, gel frames,	
990-9900-320		699.99		assorted colored gels and truss bar	
330-3300-020	Lighting Controller with101 user-			with stand adaptor.	
	programmable scenes, 10 key pad for				
	data entry, 32 channels, 4 submasters		ACCESSORIES		
		•	990-9900-280		\$169
	4 channels for special effects, MIDI		000 0000 200	of anodized aluminum alloy tubing,	
	in/out/thru ports, U.S.I.T.T. interface			100 lb. capacity.	
	protocol AMX 192 and DMX 512, audie		990-9900-360	CB-100, Four foot cross bar, drilled	69
	sync, programmable chase, Sunnplex	Superior States	330-3300-300	for fixture mounting, anodized	0.
	interface.			aluminum alloy tubing.	
			000 0000 200		67
	S (Truss or Tree Mount)		990-9900-380	PAR 38, Lighting fixture includes gel	0/
080-0310-000	PS310, Four channel (32 jumper	329.99	000 0000 500	frame, six foot cord.	
	select programmable channels), 300		990-9900-560	PAR 56, Lighting fixture includes gel	71
	watts per channel, with Sunnplex mic			frame, six foot cord.	
	cable connect system.		990-9900-640	PAR 64, Lighting fixture includes gel	76
080-0610-000	PS610, Four channel (32 jumper	379.99		frame, six foot cord.	
	select programmable channels), 600		990-9900-160	Gelpak, One each of four assorted	17
	watts per channel, with Sunnplex mic			colors.	
	cable connect system.		990-9900-140	Colormedia, One each of 20" x 24"	49
990-9900-340	PS1200, Four channel (32 jumper	439.99		gels of four assorted colors.	
	select programmable channels), 1200		990-9900-440	De-Plex 216, Rack mountable	279
	watts per channel, with Sunnplex mic			(one rack space). Translates Sunnple	ex
	cable connect system.			Multiplexing System to 16 discrete	
				channels of 0 to 10 volts. Allows Sun	n
	(Rack Mount)			controller to talk to other brand dimme	
	PSR 640, Four channels,	479.99			
080-0640-000		-10.00			
	600 watts per channel, Sunnplex				
	interface, 1 rack space.				

11

LAMPS		
990-9900-180	150, 150 Watt Par 38	12.99
990-9900-190	250 K, 250 Watt Krypton Par	35.99
990-9900-200	300 MFL, 300 Watt Par 56 Mediuim Flood	41.99
990-9900-210	500 Q, 500 Watt Quartz Par 56	91.99
990-9900-220	500 NSP, 500 Watt Par 64 Narrow Spot	66.99
990-9900-230	1,000 Q, 1,000 Watt Quartz Par 64	134.99



Effective June 1, 1990

